

1. PERFORMANCE


- 1) Measuring range : 1-16 ppm
Number of pump strokes : 3 (300mℓ)
- 2) Sampling time : 4.5 minutes/3 pump strokes
- 3) Detectable limit : 0.5 ppm
- 4) Shelf life : 2 years
- 5) Operating temperature : 0 ~ 40 °C
- 6) Temperature compensation : Necessary (See "TEMPERATURE CORRECTION TABLE")
- 7) Reading : Graduations printed on the tube are calibrated by Ethyl cellosolve at 3 pump strokes and Isoprene concentration is determined by using a conversion chart.
- 8) Colour change : Yellow → Pale blue

2. RELATIVE STANDARD DEVIATION

RSD-low : 10% RSD-mid. : 10% RSD-high : 10%

3. CHEMICAL REACTION

Chromium oxide is reduced.




4. CALIBRATION OF THE TUBE

GAS CHROMATOGRAPHY

5. INTERFERENCE AND CROSS SENSITIVITY

Substance	Interference	Coexistence
Alcohols	Similar stain is produced.	Higher readings are given.
Ethers	∕	∕
Aliphatic hydrocarbons (over C ₃)	Whole reagent is changed to Pale brown.	∕
Aromatic hydrocarbons	∕	∕
Esters	∕	∕
Ketones	∕	∕
Halogenated hydrocarbons	∕	∕

Isoprene (ppm)



No.190U Tube reading (ppm)

TEMPERATURE CORRECTION TABLE

Scale Readings (ppm)	Corrected Concentration (ppm)				
	0 °C (32 °F)	10 °C (50 °F)	20 °C (68 °F)	30 °C (86 °F)	40 °C (104 °F)
16	20.5	18.0	16.0	14.5	13.0
14	18.0	15.5	14.0	12.5	11.0
12	15.5	13.5	12.0	10.5	9.5
10	12.5	11.0	10.0	9.0	8.0
8	10.0	9.0	8.0	7.5	6.5
6	7.5	6.5	6.0	6.0	5.0
4	5.0	4.0	4.0	4.0	3.5
2	2.0	2.0	2.0	2.0	2.0
1	1.0	1.0	1.0	1.0	1.0